

Caltrans Bump Marking
(Figure 3B-29, Option B)

SPEED BUMP SIGN
TYP.

EX. CURB

EX. GUTTER
UNDULATION

EX. AC PAVEMENT

EX. CURB

12'

SPEED BUMP SIGN
W6 (15MPH) TYP.

100'±
TYP.

PLAN

EX. GUTTER

TAPER=2'

3.5"±0.2"

TACK COAT

TAPER=2'

EX. BASE


UNDULATION

EX. AC PAVEMENT

EX. CURB
& GUTTER

SECTION A-A

SEE
DETAIL



SECTION B-B

AC UNDULATION

TACK COAT

EX. AC
PAVEMENT

EX. BASE

2.6±0.2"

3.5"±0.2"

2.6"±0.2"

3'

3'

3'

3'

12'
DETAIL

NOTE: THIS PLAN IS NOT A LEGAL ENGINEERING DOCUMENT BUT AN ELECTRONIC DUPLICATE. THE SIGNED CITY OF OAKLAND STANDARD DETAILS FOR PUBLIC WORKS CONSTRUCTION IS AVAILABLE FOR PURCHASE FROM THE CONTRACT ADMINISTRATION DEPARTMENT.

CITY OF OAKLAND

DESIGN AND CONSTRUCTION SERVICES DEPARTMENT



PAVEMENT UNDULATION
Speed Bump

[Signature]
TRANSPORTATION SERVICES MANAGER

DATE: APRIL 2016
REV. DATE: _____

DWG.
T-6