



NOTE: THIS PLAN IS NOT A LEGAL ENGINEERING DOCUMENT BUT AN ELECTRONIC DUPLICATE. THE SIGNED CITY OF OAKLAND STANDARD DETAILS FOR PUBLIC WORKS CONSTRUCTION IS AVAILABLE FOR PURCHASE FROM THE CONTRACT ADMINISTRATION DEPARTMENT.

**GENERAL REQUIREMENTS:**

1. DELIVERY TAGS FOR ASPHALT CONCRETE, PORTLAND CEMENT CONCRETE AND BACKFILL MATERIAL SHALL BE SUBMITTED TO THE ENGINEER ON DEMAND. DELIVERY TAGS SHALL INDICATE THE MATERIAL SPECIFIED.
2. FINAL CONCRETE SURFACE COURSE SHALL BE ROLLED WITH CERTIFIED EIGHT-TON TANDEM ROLLER.
3. INSTALL 12" DOWELS ( #4 BAR) AT 18" OC HORIZONTALLY @ CENTER OF VERTICAL FACE OF EX. PCC SECTION. EMBED 6" INTO EX. PCC W/ EPOXY GROUT - STAGGER DOWELS

CITY OF OAKLAND      DESIGN AND CONSTRUCTION SERVICES DEPARTMENT



**SPECIAL TRENCH PAVING DETAIL**  
PORTLAND CEMENT CONCRETE STREET  
WITH ASPHALT OVERLAY OR TYPE B STREET

ENGINEERING DESIGN MANAGER  
DATE : FEBRUARY 2002      DWG.  
REV. DATE : \_\_\_\_\_      D-31