



- NOTE: 1. THE MATERIAL WILL BE ORDERED WITH EITHER A POWDER COAT FINISH OR GALVANIZED. ALL EXTERIOR SURFACES SHALL BE COATED WITH TRIGLYCIDYL ISOCYANURATE, (TGIC), POLYESTER POWDER, (OR EQUIVALENT), TO A MINIMUM DRY FILM THICKNESS OF 3 MILS. IN ACCORDANCE WITH 5A OR 5B OF ASTM-D33359. THE COLOR SHALL BE THE CITY OF OAKLAND'S, "BOXWOOD GREEN." THE INNER SURFACE SHALL BE COATED WITH A LONG OIL ALKYD TO A MINIMUM DRY FILM THICKNESS OF 2 MILS. GALVANIZING SHALL BE HOT DIPPED IN ACCORDANCE WITH ASTM-A123.
2. \*WIND LOADING SHALL BE CALCULATED BASED ON 30 POUNDS PER SQUARE FOOT OF PROJECTED AREA.
3. \*ALL DEAD-LOAD DEFLECTION CALCULATIONS SHALL INCLUDE A MINIMUM SAFETY FACTOR OF 1.5 AT ANY POINT ON THE MAST ARM OR STANDARD.

NOTE: THIS PLAN IS NOT A LEGAL ENGINEERING DOCUMENT BUT AN ELECTRONIC DUPLICATE. THE SIGNED CITY OF OAKLAND STANDARD DETAILS FOR PUBLIC WORKS CONSTRUCTION IS AVAILABLE FOR PURCHASE FROM THE CONTRACT ADMINISTRATION DEPARTMENT.

CITY OF OAKLAND	DESIGN AND CONSTRUCTION SERVICES DEPARTMENT						
	<b>STREET LIGHT STANDARD 30' MOUNTING HEIGHT WITH 20' SIGNAL MAST ARM</b>						
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">ELECTRICAL SERVICES MANAGER</td> </tr> <tr> <td style="width: 70%;">DATE: <u>OCT 95</u></td> <td style="width: 30%;">DRWG.</td> </tr> <tr> <td>REV. DATE: <u>DEC 2002</u></td> <td style="text-align: center; font-size: 1.5em;"><b>E-23</b></td> </tr> </table>		ELECTRICAL SERVICES MANAGER		DATE: <u>OCT 95</u>	DRWG.	REV. DATE: <u>DEC 2002</u>	<b>E-23</b>
ELECTRICAL SERVICES MANAGER							
DATE: <u>OCT 95</u>	DRWG.						
REV. DATE: <u>DEC 2002</u>	<b>E-23</b>						