

25' NOMINAL MOUNTING HEIGHT

POLE NUMBER SHALL CONSIST OF REFLECTIVE, ADHESIVE NUMERALS AND SHALL BE APPLIED VERTICALLY TO QUADRANT OF POLE FACING TRAFFIC. APPLY AFTER PAINT HAS DRIED. NUMBERS WILL BE FURNISHED BY THE CITY AND INSTALLED BY THE CONTRACTOR.

4" x 6 1/2" HAND HOLE WITH COVER (OPPOSITE MAST ARM UNLESS OTHERWISE SPECIFIED)

MINIMUM ALLOWABLE SECTION MODULUS AT BASE OF POLE - 4.35 CUBIC INCHES


FURNISH BASE FLANGE WITH 11" DIAMETER BOLT CIRCLE SEE DWGS. E-12, E-13 & E-14.

"POST NO BILLS" DECAL

8'-6"
5'-0"

NOTE: THE MATERIAL WILL BE ORDERED WITH EITHER A POWDER COAT FINISH OR GALVANIZED. ALL EXTERIOR SURFACES SHALL BE COATED WITH TRIGLYCIDYL ISOCYANURATE, (TGIC), POLYESTER POWDER, (OR EQUIVALENT), TO A MINIMUM DRY FILM THICKNESS OF 3 MILS. IN ACCORDANCE WITH 5A OR 5B OF ASTM-D33359. THE COLOR SHALL BE THE CITY OF OAKLAND'S, "BOXWOOD GREEN." THE INNER SURFACE SHALL BE COATED WITH A LONG OIL ALKYD TO A MINIMUM DRY FILM THICKNESS OF 2 MILS. GALVANIZING SHALL BE HOT DIPPED IN ACCORDANCE WITH ASTM-A123.

NOTE: THIS PLAN IS NOT A LEGAL ENGINEERING DOCUMENT BUT AN ELECTRONIC DUPLICATE. THE SIGNED CITY OF OAKLAND STANDARD DETAILS FOR PUBLIC WORKS CONSTRUCTION IS AVAILABLE FOR PURCHASE FROM THE CONTRACT ADMINISTRATION DEPARTMENT.

CITY OF OAKLAND	DESIGN AND CONSTRUCTION SERVICES DEPARTMENT				
	<p>STREET LIGHT STANDARD 25' MOUNTING HEIGHT WITH 15' MAST ARM</p>				
<p>ELECTRICAL SERVICES MANAGER</p> <table border="1" style="border-collapse: collapse;"> <tr> <td style="padding: 2px;">DATE : <u> OCT 95 </u></td> <td style="padding: 2px;">DRWG.</td> </tr> <tr> <td style="padding: 2px;">REV. DATE : <u> DEC 2002 </u></td> <td style="padding: 2px; font-size: 1.5em; font-weight: bold;">E-25</td> </tr> </table>		DATE : <u> OCT 95 </u>	DRWG.	REV. DATE : <u> DEC 2002 </u>	E-25
DATE : <u> OCT 95 </u>	DRWG.				
REV. DATE : <u> DEC 2002 </u>	E-25				